RAPIDGRILLE® AP


SECURITY GRILLE SYSTEMS



DURABILITY. HIGH PERFORMANCE. LOW MAINTENANCE.



INDUSTRY LEADING COMMERCIAL & INDUSTRIAL SOLUTIONS



Standard features at a glance

Max. standard width 30'4" (9,246 mm) Max. standard height 14'4" (4,369 mm)

Max. total area* 240 ft²

Curtain Galvanized steel links and rods with mill

aluminum spacer tube

Curtain pattern Straight lattice 9" center vertical links with

2" center rod spacing

Directly driven, springless steel tube roll Door roll

with integral shafts, keyed on the drive end and supported by self-aligning

greaseable sealed bearings

Hood 24 gauge black painted steel

Guides Three structural steel angles with PowderGuard® Premium powder coat

in black

Bottom bar Tubular extruded aluminum with mill finish

Standard mounting Face of wall

Direct drive, integrated gear/motor/brake Operation

assembly with hand chain override; Opening speed up to 24 inches/second

220/240V AC 1-phase;

Horsepower is appropriate to size and

weight of door

Control panel NEMA 4X rated; variable frequency drive,

self-diagnostics, built-in cycle counter, and

timer to close

Safety features Built-in braking mechanism, photoelectric

sensors with commercial grade guards, wireless, monitored sensing edge, motor

60-month on motor; 24-month on door Limited warranty

components

Options

Brick 4.5" on center vertical links with 2" Curtain pattern:

on center rods spacing

Curtain material: Mill aluminum link, galvanized steel rod,

with mill aluminum spacer tube;

Clear anodized aluminum link, galvanized steel rod, and clear anodized aluminum

spacer tube;

#4 or #2B stainless steel link, rod, and

spacer tube

PowderGuard® Premium finish **Guides:** PowderGuard® Zinc or Textured finish

24 gauge powder coated steel, stainless Hood:

steel with brush finish, powder coated

aluminum

Loop detectors, radio control, push Actuators:

buttons, motion detectors and pull cords

(wireless accessories available)

^{*} Dependent upon the curtain material and pattern. Consult factory for sizes not listed above.




The solution that answers demanding application needs

The RapidGrille® AP Security Grille System was developed to supply advanced performance in industrial, security and general commercial applications where tenants' security, long term asset value and minimized interruption to facility access are primary concerns.

The RapidGrille® AP system's advanced performance design answers the demand for more in reliability, durability and efficiency. Ideal applications include the following:

- Parking garage facilities
- Industrial manufacturing facilities
- Government facilities
- Public facilities

Grille data and pattern



| Wall opening height | Dimension A |
|---------------------|-------------|
| Thru 6' | 14" |
| Thru 10' | 16" |
| Thru 14' | 18" |

Note: These products allow air infiltration and are not weather tight.

Benefits

The RapidGrille® Advanced Performance Security Grille provides facilities with maximized air movement and visual access while delivering more safety features than a standard security grille. The reliable springless design and operation provides reliable performance and asset longevity.

The continuous rod design combined with the high strength curtain materials of the RapidGrille® AP increases the durability and security of this system.





Architect's Corner

A resource for architects, containing comprehensive technical and resource materials to support your project, including drawings and specifications for commercial doors.

overheaddoor.com

The original, innovative choice for unequalled quality and service.

Overhead Door pioneered the upward-acting door industry, inventing the first upward-acting door in 1921 and the first electric door operator in 1926. Today, we continue to be the industry leader through the strength of our product innovation, superior craftsmanship and outstanding customer support, underscoring a legacy of quality, expertise and integrity. That's why design and construction professionals specify Overhead Door products more often than any other brand. Our family of over 400 Overhead Door Distributors across the U.S. and Canada not only share our name and logo, but also our commitment to excellence.













INDUSTRY LEADING **COMMERCIAL & INDUSTRIAL SOLUTIONS**

2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067 1-800-929-DOOR • sales@overheaddoor.com overheaddoor.com